

Zelio Timer Relays

Modular single, dual or multifunction relays with diagnostic button and dial pointer, relay output, width 22.5 mm/0.886 in.

Output 1 C/O and 2 C/O contacts

- Multifunction, dual function, or single function
- Multiple timing ranges (up to 10 switchable ranges)
- Multivoltage
- 1 or 2 relay outputs: 8 A - 250 V
- Screw terminals
- State indication by LED
- Option of supplying a load in parallel
- 3-wire sensor control option
- Diagnostic button (1) and dial pointer LED indicator



RE22R2QTMR



RE22R2KMR



RE22R2QEMR



RE22R2HMR



RE22R1MYMR

References

Single function

Timing ranges	Functions	No. of relay outputs	Voltages	Reference	Weight
			V		
10 time range selection 1 s, 3 s, 10 s, 30 s, 100 s, 300 s, 30 min, 300 min, 30 h, 300 h	Ac	2	~ 24...240	RE22R2ACMR	0.105/ 0.231
	Qg	2	~ 24...240	RE22R2QGMR	0.105/ 0.231
	Qt	2	~ 24...240	RE22R2QTMR	0.105/ 0.231
7 time range selection 1 s, 3 s, 10 s, 30 s, 100 s, 300 s, 10 min	K	1	~ 24...240	RE22R1KMR	0.100/ 0.220
		2	~ 24...240	RE22R2KMR	0.100/ 0.220
7 time range selection 0.5 s, 1 s, 3 s, 10 s, 30 s, 100 s, 300 s	Qc	1	~ 24/~ 24...240	RE22R1QCMU	0.080/ 0.176
Single range selection 30 s	Qe	2	~ 24...240	RE22R2QEMR	0.090/ 0.198
		2	~ 380...415	RE22R2QEMT	0.090/ 0.198

Dual function

10 time range selection 1 s, 3 s, 10 s, 30 s, 100 s, 300 s, 30 min, 300 min, 30 h, 300 h	A, Aw	1	~ 24...240	RE22R1AMR	0.100/ 0.220
		2	~ 24...240	RE22R2AMR	0.105/ 0.231
	C, Ct	1	~ 24...240	RE22R1CMR	0.100/ 0.220
		2	~ 24...240	RE22R2CMR	0.105/ 0.231
	Ac, Act	1	~ 24...240	RE22R1ACMR	0.100/ 0.220
	Ak, Akt	1	~ 24...240	RE22R1AKMR	0.100/ 0.220
	D, Dw	1	~ 24...240	RE22R1DMR	0.100/ 0.220
		2	~ 24...240	RE22R2DMR	0.105/ 0.231
	H, Hw	1	~ 24...240	RE22R1HMR	0.100/ 0.220
		2	~ 24...240	RE22R2HMR	0.105/ 0.231
	Wt, W	2	~ 24...240	RE22R2MWMR	0.105/ 0.231
7 time range selection 0.5 s, 1 s, 3 s, 10 s, 30 s, 100 s, 300 s	K, He	1	~ 24...240	RE22R1MKMR	0.100/ 0.220
10 time range selection 1 s, 3 s, 10 s, 30 s, 100 s, 300 s, 30 min, 300 min, 30 h, 300 h	A, At, Aw	1	~ 24...240	RE22R1MAMR	0.100
	A, At, Aw, Ac, Act, C, Ct, D, Dt, Dw, Di, Dit, Diw, H, Ht, Hw, W, Wt,	1	~ 24...240	RE22R1MYMR	0.100/ 0.220
	A, At, Aw, C, Ct, D, Dt, Dw, Di, Dit, Diw, H, Ht, Hw, Qg, Qgt, Qt, Qtt, W, Wt	2	~ 24...240	RE22R2MYMR	0.105/ 0.231
	L, Li, Lt, Lit	1	~ 24...240	RE22R1MLMR	0.100/ 0.220

(1) The diagnostic button is not available for the K function related references (RE22R1KMR, RE22R2KMR and RE22R1MKMR).

Zelio Timer Relays

Modular single, dual or multifunction relays, relay output, width 22.5 mm/0.886 in.

Output 1 C/O and 2 C/O contacts

- Multifunction, dual function or single function
- Multiple timing ranges (7 switchable ranges)
- Multivoltage
- 1 or 2 relay outputs: 8 A - 250 V
- Screw or spring terminals
- State indication by LED
- Option of supplying a load in parallel
- 3-wire sensor control option



RE22R1QMU



RE22R2AMU



RE22R2MMU

References

Multi function

Timing ranges	Functions	No. of relay outputs	Voltages	Reference	Weight
			V		kg/lb
7 time range selection 1 s, 10 s, 1 min, 10 min, 1 h, 10 h, 100 h	Q	1	≡ 24/∼ 24...240	RE22R1QMU	0.090/ 0.198
		1	∼ 230/380	RE22R1QM \bar{Q}	0.090/ 0.198

Dual function

7 time range selection 1 s, 10 s, 1 min, 10 min, 1 h, 10 h, 100 h	A, At	2	≡ 24/∼ 24...240	RE22R2AMU	0.090/ 0.198
--	-------	---	-----------------	-----------	-----------------

Multi function

1 s, 10 s, 1 min, 10 min, 1 h, 10 h, 100 h	A, At, B, C, H, Ht, Di, D, Ac, Bw	2	≡ 24/∼ 24...240	RE22R2MMU (1)	0.090/ 0.198
			∼ 12	RE22R2MJU (1)	0.090/ 0.198
			∼ 12...240	RE22R2MMW (1)	0.090/ 0.198
	Ad, Ah, N, O, P, Pt, Tl, Tt, W	2	≡ 24/∼ 24...240	RE22R2MXMU (1)	0.090/ 0.198

(1) Connection by screw terminals.